



SOLID STATE LED LIGHTING

· COMMERCIAL · INDUSTRIAL · RESIDENTIAL

COOLCORE ELECTRONIC BALLAST COMPATIBLE LED TUBES

120 or 347V

5 YEAR WARRANTY



PLUG-N-PLAY

ELECTRONIC BALLAST COMPATIBLE 100-347V 5 YEAR WARRANTY IES, LM79/LM80 AVAILABLE

Model No.	Length	Color	LED QTY	Voltage (V)	Power(W)	Lumen(lm)	CRI	PF	THD	LIST PRICE
CFT82FT120BCNW	2FT	5000K	60	100-347V	9	900lm±10%	<80	>0.9	<20%	Enquire
CFT82FT120BCWW	2FT	4000K	60	100-347V	9	900lm±10%	<80	>0.9	<20%	Enquire
CFT83FT120BCNW	3FT	5000K	96	100-347V	14	1600lm±10%	<80	>0.9	<20%	Enquire
CFT83FT120BCWW	3FT	4000K	96	100-347V	14	1600lm±10%	<80	>0.9	<20%	Enquire
CFT84FT120BCNW	4FT	5000K	120	100-347V	18	2000lm±10%	<80	>0.9	<20%	Enquire
CFT84FT120BCWW	4FT	4000K	120	100-347V	18	2000lm±10%	<80	>0.9	<20%	Enquire
CFT85FT120BCNW	5FT	5000K	144	100-347V	22	2400lm±10%	<80	>0.9	<20%	Enquire
CFT85FT120BCWW	5FT	4000K	144	100-347V	22	2400lm±10%	<80	>0.9	<20%	Enquire
CFT86FT120BCNW	6FT	5000K	192	100-347V	24	2800lm±10%	<80	>0.9	<20%	Enquire
CFT86FT120BCWW	6FT	4000K	192	100-347V	24	2800lm±10%	<80	>0.9	<20%	Enquire
CFT88FT120BCNW	8FT	5000K	240	100-347V	36	3900lm±10%	<80	>0.9	<20%	Enquire
CFT88FT120BCWW	8FT	4000K	240	100-347V	36	3900lm±10%	<80	>0.9	<20%	Enquire

Double Ended Power Input - Compatible with Electronic Ballast only

ALL ITEMS - MINIMUM ORDER 25 PIECES - CASE LOT(25 pieces) QUANTITIES ONLY

COLOUR OPTIONS	LENS OPTIONS	PIN OPTIONS
WARM WHITE	TRANSPARENT	STANDARD IS G13 Bi-pin
NATURAL W/WHITE	FROSTED	F8, R17D HO or Rotating are available
CUSTOM COLOURS AVAILABLE	RIBBED	



PRODUCT DIMENSIONS		
Size	Length Excluding Pins	Length Including Pins
2FT	588mm(L)×φ26mm	602mm(L)×φ26mm
3FT	894mm(L)×φ26mm	908mm(L)×φ26mm
4FT	1198mm(L)×φ26mm	1212mm(L)×φ26mm
5FT	1498mm(L)×φ26mm	1512mm(L)×φ26mm
6FT	1760mm(L)×φ26mm	1774mm(L)×φ26mm
8FT	2369mm(L)×φ26mm	2383mm(L)×φ26mm

Note: Metric Sizes are available



HEAD OFFICE - EDMONTON

18805 87A Ave
Edmonton AB T5T 5Z7
ph: 780 - 905 - 3970
Fax 780-489-9441

BC REGIONAL HEAD OFFICE

9338 Lochside Drive
Sidney, BC V8L 1N7
PH: 250 - 213-5070
Fax 250 - 656-1392

